



Made exclusively for NEMEON Members by APOC

**PROFESSIONAL-GRADE PRODUCTS**

**LionGUARD #30 Roofing Felt (ASTM D4869 TYPE 2)**

**PRODUCT DESCRIPTION**

LionGUARD asphalt saturated felts are made from virgin and recycled wood pulp that is saturated with a premium asphalt. The saturation of the organic felt mat promotes a greater resistance to vapor transmission, a heavier sheet, greater tensile strength, and more resistance to tear when being installed.

**USES**

LionGUARD organic felts are excellent underlayments for steep-slope roofing such as 3-tab shingles, wood shakes, and tiles. In addition, these felts can be installed under all types of building materials, flooring, and siding including stucco, aluminum, vinyl, and wood. LionGUARD organic felts are excellent secondary protection barriers against wind, moisture, and other environmental elements.

**PRODUCT SPECIFICATIONS**

**TYPICAL TEST CRITERIA FOR ASTM D4869 TYPE 2 FELTS**

Roll width, minimum inches	36
Area of roll, minimum sf	216
Net mass saturated felt, min lb/100 sf	13
Mass of saturant, minimum lb/100 sf	6
Mass of desaturant felt, min lb/100 sf	5
Ash, maximum percent	10
Pounds Roll Weight	28
Rolls per Pallet	42

**NEMEON, Inc.** | 6043 Hudson Rd. Suite 350 Woodbury, MN 55125  
Phone: (651) 788-7810 Fax: (651) 788-7807 | [www.nemeon.com](http://www.nemeon.com)

**APOC** | 5903 Paramount Blvd, Long Beach, CA 90805  
Phone: 1-800-562-5669 | [www.apoc.com](http://www.apoc.com)

