



Made exclusively for NEMEON Members by APOC

PROFESSIONAL-GRADE PRODUCTS



## LionGUARD Aerosol Asphalt Primer

### COMPLIANCE

Exceeds performance requirements of ASTM D41. MIAMI-DADE APPROVED. ASBESTOS FREE.

### PRODUCT DESCRIPTION

LionGUARD Asphalt Primer is a professional grade primer formulated with a high penetrating solvent and select asphalt. It is designed to promote superior adhesion of roofing materials. LionGUARD Primer can be used to prime newly laid concrete or cement decks, gypsum, masonry thermal insulation and weathered roofing prior to applying built-up roofing. LionGUARD Primer can also be applied to weathered roofing prior to application of black or reflective coatings. Allow primer to cure 30 days prior to application of reflective coatings.

### PREPARATION

All surfaces must have proper drainage and be clean, dry and free of surface rust and any other foreign matter. Repair all problem areas with an approved Lion Guard Cement. MIX THOROUGHLY. DO NOT HEAT OR THIN. DO NOT APPLY IF RAIN IS EXPECTED WITHIN 24 HOURS.

### APPLICATION

For exterior use only. Protective clothing, gloves and eyewear should be used during application of these products. Surface must be clean and dry before painting. Protect surrounding areas from spray mist. For best result, use when can is between 50 °F and 90 °F. Shake can at least one minute after rattle is heard and occasionally during use. Spray surface with steady even strokes at a distance of 2 to 10 inches. Multiple coats may be applied, allowing 20 to 30 minutes between coats. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

### APPLICATION RATE

Approximately 50 sq. ft. per can depending on porosity of surface and method of application. Work material to a smooth and even consistency. Avoid excessive build up or puddles of primer. DO NOT APPLY TO ASPHALT DRIVEWAYS.

### CLEAN UP

Clean tools with paint thinner or mineral spirits.

### PRODUCT SPECIFICATIONS

Weight Per Gallon	7.0 - 8.0 lbs.
Residue by Evaporation, %	52 min.
Application Tool	Spray
Tack Time (50% Relative Humidity, 70 °F)	30 minutes
Full Cure (50% Relative Humidity, 70 °F)	24 - 48 hours
Application Temperatures	35 °F - 120 °F
Clean-up Tools	Paint Thinner, Mineral Spirits

### Approx. Shipping Weights: (Note: all approx. weights include container)

17 oz. spray can	1 lb.
------------------	-------

### STORAGE & HANDLING PRECAUTIONS

Ensure product is secure for transport. Do not allow to roll around in cargo portion of vehicle as it could damage container and allow escape of pressurized gas and material. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110 °F. Exposure to heat or prolonged exposure to the sun may cause bursting. This manufacturer also disclaims liability for flat surface application where poor drainage or moisture may prevail.

NEMEON, Inc. | 6043 Hudson Rd. Suite 350 Woodbury, MN 55125  
Phone: (651) 788-7810 Fax: (651) 788-7807 | www.nemeon.com

APOC | 5903 Paramount Blvd, Long Beach, CA 90805  
Phone: 1-800-562-5669 | www.apoc.com

