



Made exclusively for NEMEON Members by APOC

**PROFESSIONAL-GRADE PRODUCTS**



## LionGUARD Flashing Cement

### COMPLIANCE

Exceeds performance requirements ASTM D3409, ASTM D4586, TYPE I. MIAMI-DADE APPROVED. ASBESTOS FREE.

### PRODUCT DESCRIPTION

LionGUARD Flashing Cement is a professional grade, all weather flashing cement that provides a multi-purpose mastic for repairs, maintenance and detail work. LionGUARD Flashing Cement is manufactured with premium grade asphalt, solvent and fibers and is crafted to a smooth and butter like consistency. LionGUARD Flashing Cement is excellent for setting and repairing flashing, gutters, sills, curbs, copings, chimneys, skylights, seams, terminations and many other roofing and waterproofing applications.

### PREPARATION

All surfaces must be clean, have proper drainage and be free of surface rust and any other foreign matter. DO NOT HEAT OR THIN.

### FOR BEST RESULTS

Apply when surface temperatures are between 20 °F and 50 °F. In colder weather product should be stored in heated room (65 °F to 80 °F.) at least 24 hours prior to application. Application in temperature over recommended range may cause product to run or drip. After a minimum of 45 days cure time, apply a reflective coating. This will greatly extend the life of the roof.

### APPLICATION

For exterior use only. Protective clothing, gloves and eyewear should be used during application of this product. Apply with a trowel or putty knife. Work material to an even consistency over and into the area to be repaired. Apply 1/8" to 1/4" thick, two to three inches beyond the problem area. For cracks or holes 1/4" to 3/4" wide, press a strip of Glass Fabric into the cement and cover with an additional layer of roof cement. Form a cant with the cement around chimneys and other roof projections. Coverage rate is approximately 12 1/2 sq. ft. when applied 1/8" thick.

### CLEAN UP

Clean tools with paint thinner or mineral spirits.

### PRODUCT SPECIFICATIONS

Weight Per Gallon	8.0 - 9.0 lbs.
Residue by Evaporation, %	70 min.
Application Tool	Trowel
Cure Time (50% Relative Humidity, 70 °F)	4 - 8 hours
Full Cure (50% Relative Humidity, 70 °F)	24 - 48 hours
Application Temperatures	35 °F - 120 °F
Clean-up Tools	Paint Thinner, Mineral Spirits

### Approx. Shipping Weights: (Note: all approx. weights include container)

3 gallons (11.3L)	28 lbs.
5 gallons (18.9L)	45 lbs.

### STORAGE & HANDLING PRECAUTIONS

When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110 °F. This manufacturer also disclaims liability for flat surface application where poor drainage or moisture may prevail. For exterior use only.

NEMEON, Inc. | 6043 Hudson Rd. Suite 350 Woodbury, MN 55125  
Phone: (651) 788-7810 Fax: (651) 788-7807 | [www.nemeon.com](http://www.nemeon.com)

APOC | 5903 Paramount Blvd, Long Beach, CA 90805  
Phone: 1-800-562-5669 | [www.apoc.com](http://www.apoc.com)

