



Made exclusively for NEMEON Members by APOC

PROFESSIONAL-GRADE PRODUCTS

LionGUARD All Weather SBS Modified Cement

COMPLIANCE

Exceeds performance requirements of ASTM D3409 and ASTM D4586, TYPE I. MIAMI-DADE APPROVED. ASBESTOS FREE.

PRODUCT DESCRIPTION

LionGUARD All Weather SBS Modified Cement is a high Performance, rubberized flashing cement specially formulated for the professional roofer. It is an extremely versatile mastic that provides superior adhesion and durability. This product is great for use in wet or dry conditions and easily bonds under water. and is ideal for temporary or permanent repairs. LionGUARD All Weather SBS Modified Cement is the ultimate repair compound and can be used to repair splits, seams, cracks and leaks in built-up, shingle, gravel, concrete and most APP and SBS membranes.

PREPARATION

All surfaces must be clean, have proper drainage and be free of surface rust, dust and any other foreign matter. After a minimum of 45 days cure time, apply a reflective roof coating. This will greatly extend the life of the cement. DO NOT HEAT OR THIN.

FOR BEST RESULTS

Apply when surface temperatures are between 50 °F and 120 °F. In colder weather, product should be stored in heated room (65 °F to 80 °F.) at least 24 hours prior to application. Product formulated to be used year round.

APPLICATION

For exterior use only. Protective clothing, gloves and eyewear should be used during application of these products. Apply with a trowel or putty knife. Work material to an even consistency over and into the area to be repaired. Using the “3-course” method, apply cement 1/8” thick, two or three inches beyond the problem area. Then reinforce the repair and embed a strip of polyester, fiberglass or cotton reinforcing fabric. Brush fabric to ensure it is fully saturated from the bottom side up. Finally, cover the fabric with an additional layer of cement. Form a feathered edge with cement where chimneys, vent pipes, and other projections meet the roof line. For best results, protect completed repair with a reflective coating. Coverage rate is approximately 12 1/2 sq. ft. per gallon when applied 1/8” thick.

CLEAN UP

Clean tools with paint thinner or mineral spirits.



PRODUCT SPECIFICATIONS

Weight Per Gallon	8.0- 9.0 lbs.
Adhesion Underwater	Excellent
Application Tool	Trowel
Application Temperatures	35 °F - 120 °F
Clean-up Tools	Paint Thinner, Mineral Spirits

Approx. Shipping Weights: (Note: all approx. weights include container)

10.1 oz. tube (300 ml)	0.75 lbs.
1 gallon (3.8L)	10 lbs.
3 gallons (13.2 L)	31 lbs.
5 gallons (18.9 L)	46 lbs.

STORAGE & HANDLING PRECAUTIONS

When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110 °F.

NEMEON, Inc. | 6043 Hudson Rd. Suite 350 Woodbury, MN 55125
Phone: (651) 788-7810 Fax: (651) 788-7807 | www.nemeon.com

APOC | 5903 Paramount Blvd, Long Beach, CA 90805
Phone: 1-800-562-5669 | www.apoc.com

