

LionGUARD MODIFIED ADHESIVE TROWEL GRADE



PRODUCT DESCRIPTION

LionGuard Modified Bitumen Adhesive Trowel Grade is a heavy mastic, modified SBS asphalt, asbestos-free, cold applied adhesive for use in adhering SBS modified bitumen membrane base and ply sheets as well as making repairs on existing modified bitumen applications. May also be used with conventional built-up ply sheets and granulated cap sheets. The unique qualities of this adhesive produce a bond of excellent strength. Meets ASTM D-3019 Type III.

ADVANTAGES

- » No need for torches or asphalt kettles
- » Produces a tough bond
- » Elastomeric film moves with membranes

INSTALLATION

All surfaces should be dry, clean and free from dirt, dust, oil, grease and debris. For vertical applications and at seams and endlaps, apply in a 1/8" thickness (approximately 8 gallons per 100 square feet) using a serrated trowel. Apply adhesive in a uniform and continuous film to ensure even coverage. Allow adhesive to have an open time of 15 minutes before installing membranes.

CLEAN UP & STORAGE

Clean tools and equipment with mineral spirits or similar solvent. Use caution when handling combustible materials. Store in a dry area where the temperature is between 50°F and 100°F.

PACKAGING



5 Gallon

CAUTION COMBUSTIBLE

Do not use near open flame or fire. Avoid breathing solvent fumes and prolonged contact with skin. Do not use in a confined space. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children. Do not thin. Keep container closed when not in use. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.