

S35/200LG: Stainless Steel Detail Torch Kit



COMPONENTS

620E	Handle with Swivel Attachment
35SL200	200 mm Torch Assembly with Stand
530E	30' Hose U/L listed
915	30-60 PSI Regulator U/L Listed
0702500	Flint Striker

CHARACTERISTICS

Length	200 mm
Weight	1.59 lbs
Diameter of Torch	35 mm
Flame Length	25.6"
Max. Capacity BTU/hr	105,000@ 60 PSI
Gas Consumption lbs/hr	4.2 lbs/hr @ 30 PSI

DESCRIPTION: Powerful and durable, our stainless steel torch kits include all of the elements needed for modified membrane applications. These kits are lightweight and easy to handle, plus they come completely assembled for immediate use.

S60/400LG: Stainless Steel Field Torch Kit



COMPONENTS

620E	Handle with Swivel Attachment
100SL400	400 mm Torch Assembly with Stand
530E	30' Hose U/L listed
915	30-60 PSI Regulator U/L Listed
0702500	Flint Striker

CHARACTERISTICS

Length	400 mm
Weight	1.81 lbs
Diameter of Torch	60 mm
Flame Length	31.5"
Max. Capacity BTU/hr	348,000 @ 60 PSI
Gas Consumption lbs/hr	8.1 lbs/hr @ 30 PSI

To Order, Please Contact
Guilbert Express Customer Service:
 Toll-free: 1-888-628-6343
 Fax: 1-866-404-2607
 Email: customer_service@guilbert-express.com
guilbert-express.com

S60/35LG: Stainless Steel Combo Torch Kit



COMPONENTS

620E	Handle with Swivel Attachment
100SL400	400 mm Torch Assembly with Stand
530E	30' Hose U/L listed
915	30-60 PSI Regulator U/L Listed
0702500	Flint Striker



620E	Handle with Swivel Attachment
35SL200	200 mm Torch Assembly with Stand
36201	Quick Coupling 9/16 Female
36202	2 Quick Couplings 9/16 Male

CHARACTERISTICS



For torch characteristics, please refer to the individual kit information.

Distributor Name